

AIR CONDITIONER PRODUCT LINE

| Model | BTU/Hour | Voltage/ Phase/Hz | Running Amps | Max. Ambient Temp | Max. Integrated Heat (Watts) | H x W x D | Unit Weight |
|----------|----------|----------------------|-----------------|-------------------------|---------------------------------------|------------------------|----------------|
| CS011D48 | 1,000 | 48 VDC | 3.5 | 125°F | NA | 17" x 7" x 7" | 31 |
| CS011126 | 1,000 | 120/1/60 | 2.7 | 131°F | 350 | 17" x 7" x 7" | 31 |
| NE010126 | 1,000 | 120/1/60 | 3.44 | 125°F | NA | 22" x 11.8" x 8.5" | 51 |
| NE010236 | 1,000 | 230/1/60 | 2.67 | 125°F | NA | 22" x 11.8" x 8.5" | 53 |
| NE015126 | 1,500 | 120/1/60 | 3.44 | 125°F | NA | 22" x 11.8" x 8.5" | 51 |
| NE015236 | 1,500 | 230/1/60 | 2.67 | 125°F | NA | 22" x 11.8" x 8.5" | 53 |
| CS020126 | 2,000 | 120/1/60 | 4.1 | 131°F | 500 | 20" x 10" x 10" | 44 |
| CS020236 | 2,000 | 230/1/60 | 2.0 | 131°F | 500 | 20" x 10" x 10" | 49 |
| NE020126 | 2,000 | 120/1/60 | 3.3 | 134°F | 1000 | 32" x 11.8" x 9.5" | 60 |
| NE020236 | 2,000 | 230/1/60 | 3.07 | 125°F | 1000 | 32" x 11.8" x 9.5" | 72 |
| NE02S486 | 2,000 | 480/1/60 | 0.87 | 134°F | 1000 | 32" x 11.8" x 15.1" | 94 |
| NE020486 | 2,000 | 480/1/60 | 0.87 | 134°F | 1000 | 38" x 11.8" x 9.5" | 94 |
| NE030126 | 3,000 | 120/1/60 | 4.86 | 140°F | 1000 | 32" x 11.8" x 9.5" | 70 |
| NE030236 | 3,000 | 230/1/60 | 3.07 | 125°F | 1000 | 32" x 11.8" x 9.5" | 72 |
| NE03S486 | 3,000 | 480/1/60 | 1.28 | 140°F | 1000 | 32" x 11.8" x 15.1" | 103 |
| NE030486 | 3,000 | 480/1/60 | 1.28 | 140°F | 1000 | 38" x 11.8" x 9.5" | 103 |
| NE040D48 | 4,000 | 48 VDC | 25.3 | 131°F | NA | 35.27" x 11.8" x 9.5" | 103 |
| NE040126 | 4,000 | 120/1/60 | 6.76 | 125°F | 1000 | 32" x 11.8" x 9.5" | 70 |
| NE040236 | 4,000 | 230/1/60 | 3.07 | 125°F | 1000 | 32" x 11.8" x 9.5" | 72 |
| NE04S486 | 4,000 | 480/1/60 | 1.69 | 125°F | 1000 | 32" x 11.8" x 15.1" | 103 |
| NE040486 | 4,000 | 480/1/60 | 1.69 | 125°F | 1000 | 38" x 11.8" x 9.5" | 103 |
| NE050126 | 5,000 | 120/1/60 | 6.14 | 140°F | 1000 | 36" x 11.8" x 15.1" | 97 |
| NE050236 | 5,000 | 230/1/60 | 3.76 | 140°F | 1000 | 36" x 11.8" x 15.1" | 92 |
| NE050486 | 5,000 | 480/1/60 | 1.9 | 140°F | 1000 | 44.63" x 11.8" x 15.1" | 136 |
| NE060126 | 6,000 | 120/1/60 | 7.83 | 125°F | 1000 | 36" x 11.8" x 15.1" | 97 |
| NE060236 | 6,000 | 230/1/60 | 4.8 | 125°F | 1000 | 36" x 11.8" x 15.1" | 98 |
| NE060486 | 6,000 | 480/1/60 | 2.4 | 125°F | 1000 | 44.63" x 11.8" x 15.1" | 142 |

AIR CONDITIONER PRODUCT LINE

(CONTINUED)

| Model | BTU/Hour | Voltage/ Phase/Hz | Running Amps | Max. Ambient Temp | Max. Integrated Heat (Watts) | H x W x D | Unit Weight |
|----------|----------|----------------------|-----------------|-------------------------|---------------------------------------|-------------------------|----------------|
| TM061126 | 6,000 | 120/1/60 | 10.6 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 111 |
| TM061236 | 6,000 | 230/1/60 | 6.0 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 111 |
| TM061486 | 6,000 | 480/1/60 | 2.9 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 154 |
| NE080126 | 8,000 | 120/1/60 | 7.83 | 125°F | 1000 | 36" x 11.8" x 15.1" | 102 |
| NE080236 | 8,000 | 230/1/60 | 4.8 | 125°F | 1000 | 36" x 11.8" x 15.1" | 103 |
| NE080486 | 8,000 | 480/1/60 | 2.4 | 125°F | 1000 | 44.63" x 11.8" x 15.1" | 142 |
| TM081126 | 8,000 | 120/1/60 | 11.6 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 111 |
| TM081236 | 8,000 | 230/1/60 | 7.0 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 111 |
| TM081486 | 8,000 | 480/1/60 | 3.5 | 131°F | 1000 | 15.6" x 26.3" x 20.2" | 154 |
| HC101126 | 10,000 | 120/1/60 | 19.4 | 131°F | 1500 | 48" x 15.9" x 15.1" | 162 |
| HC101236 | 10,000 | 230/1/60 | 8.2 | 131°F | 1500 | 48" x 15.9" x 15.1" | 166 |
| HC101486 | 10,000 | 480/1/60 | 4.1 | 131°F | 1500 | 57.6" x 15.9" x 15.1" | 232 |
| HC121126 | 12,000 | 120/1/60 | 19.4 | 131°F | 1500 | 48" x 15.9" x 15.1" | 167 |
| HC121236 | 12,000 | 230/1/60 | 8.2 | 131°F | 1500 | 48" x 15.9" x 15.1" | 163 |
| HC121486 | 12,000 | 480/1/60 | 4.1 | 131°F | 1500 | 57.6" x 15.9" x 15.1" | 237 |
| HC151236 | 15,000 | 230/1/60 | 9.93 | 140°F | 1500 | 48" x 15.9" x 15.1" | 170 |
| HC151486 | 15,000 | 480/1/60 | 5.21 | 140°F | 1500 | 57.6" x 15.9" x 15.1" | 247 |
| HC201236 | 20,000 | 230/1/60 | 19.26 | 129°F | 1500 | 56.1" x 23" x 15" | 230 |
| HC201486 | 20,000 | 480/1/60 | 9.62 | 129°F | 1500 | 65.7" x 23" x 15" | 362 |
| HC20C236 | 20,000 | 230/1/60 | 12.47 | 140°F | 1500 | 48" x 15.86" x 15.03" | 170 |
| HC20C486 | 20,000 | 480/1/60 | 6.3 | 140°F | 1500 | 57.6" x 15.86" x 15.03" | 247 |